




# 15" Panel PC / Monitor

## Mounting systems: Panel Mount / Rack Mount / open frame

- Mechanical designs: Panel Mount, Rack Mount and open frame
- Touchscreen: resistive, glass-film-glass (GFG)
- Protection class: front side IP65 (dust - tight, protection against splash water)
- Processor: Intel® ATOM™ N2600 / N2800, Intel® Bay Trail-M N2930 (fanless) or Intel® Core™ i3
- Extended temperature range -20°C to +70°C
- Option: Sunlight readable display by Optical Bonding



## Description

The rugged and durable industrial Panel PCs and monitors of product line "Lizard" has been designed for installation in existing housing systems for example control cabinets / consoles, 19"Racks, ...

They are divided into the mechanical designs Panel Mount, Rack Mount and open frame. The front plates are made of aluminium, steel plate or stainless steel with IP65 protection and can be customized individually, for example marked with your own logo.

The hardware is constantly state of the art and provides enough space for future designs and applications. Individual product adaptations / solutions can be realised in accordance with customer requirements.

## Applications

- Plant and machine engineering
- Industrial automation
- Food & Beverage
- Safety engineering
- Warehouse & Logistics

**Different versions** (in each case available as Panel PC or Monitor - individually configurable)



**Panel Mount**  
 - Front plate individually adaptable  
 - material / size according to customer specifications  
 (Example in stainless steel)



**Rack Mount**  
 - 19"Rack-Front plate in various rack units (HE)  
 - Standard: 6 HE / 7HE  
 (Example in RAL7035)



**Open Frame**  
 - Metal chassis  
 - Drawings: see from page 3





# 15" Panel PC / Monitor

Mounting systems: Panel Mount / Rack Mount / open frame

## Specifications

	Monitor	Panel PC
Display	15"LED - 400 cd/m <sup>2</sup> - 1024 x 768	
Viewing Angle	H/V 160°/160°	
<b>System</b>		
CPU	-	N2600 -1.6 GHz   N2800 - 1.86 GHz   N2930 - 1.83 GHz   Intel® Core™ i3
Chipset	-	Intel® NM10 EXPRESS   -   Intel® QM77
Memory	-	DDR3 max. 2GB   DDR3 max. 4GB   DDR3L max. 4GB   DDR3 max. 8GB
Storage	-	1x 2,5" SSD / HDD (optional) - 24/7 continuous operation
Connections I/O	1 x VGA 1 x DVI (other connections on request!)	2 x USB 1 x LAN 1 x RS 232/422/485 (other connections on request!)
Expansion interface	-	1x Mini PCI-e (internal)
Touchscreen	Resistive / GFG (optional)	
Operating voltage	12V DC / 24V DC / 110-240V AC (optional)	
Dimension (WxHxD)	see page 4 to 6	see page 7
<b>Front plate</b> (optional)		
Panel Mount	stainless steel V2A (IP65 on front)	
Panel Mount	Material / size / RAL according customer requirements	
Rack Mount	Material / HE / RAL according customer requirements	
Weight	~ 5 kg	~ 6 kg (depending on the version)
<b>Work environment</b>		
Temperature range	Operating	0° to +50° C
	Storage	-20° to +60° C
Extended temperature range	(optional)	-20° to +70° C
Relative air humidity	Operating	10% ~ 95% @ 40° C (non-condensing)
	Storage	5% ~ 95%
Vibration	Operating	2 - 9 Hz: Amplitude 3mm / 9 ~ 200Hz: 1G
	Storage	2 - 8 Hz: Amplitude 7,5mm / 8 ~ 200Hz: 2G / 200 ~ 500Hz: 4G
Protection class	Front side IP65 (Panel Mount / Rack Mount)	
Certification	CE, ROHS, IP	
Systems software	Windows XP / Windows 7 / Windows 8.1 (Desktop- and Embedded-versions) / LINUX	





# 15" Panel PC / Monitor

Mounting systems: Panel Mount / Rack Mount / open frame

## Maßzeichnungen

### Monitor / Panel PC

Version "open frame"

→ Monitor: page 4



Version "Panel Mount" with threaded bolts

→ Monitor: page 5



Version "Panel Mount" with clamp fastening

→ Monitor: page 6

→ Panel PC: page 7






# 15" Monitor

Mounting systems: Panel Mount / Rack Mount / open frame

## Dimensional drawing

Monitor „open frame“ - 345.5 x 262.0 x 53.0 mm (WxHxD)






# 15" Monitor

Mounting systems: Panel Mount / Rack Mount / open frame

## Dimensional drawing

Monitor „Panel Mount“ with threaded bolts - 410.0 x 335.0 x 55.0 mm (WxHxD)






# 15" Monitor

Mounting systems: Panel Mount / Rack Mount / open frame

## Dimensional drawing

Monitor „Panel Mount“ with clamp fastening - 410.0 x 335.0 x 55.0 mm (WxHxD)





# 15" Panel PC

Mounting systems: Panel Mount / Rack Mount / open frame

## Dimensional drawing

Panel PC „Panel Mount“ with clamp fastening - 400.0 x 320.0 x 71.5(+34) mm (WxHxD)

